

## FORTIS XP-3000 Series



Clear LED indicator panel



### Printer

3" thermal printer (60mm/sec)



### MSR

2 or 3 tracks & JIS-II

## Features

- Intel Pine View processor with dual core option.
- One touch power switch design provides convenience control for terminal and printer.
- 3 inch Thermal printer with excellent paper handling.
- Integrated system including touch screen, thermal printer and MSR.
- LCD panel with easy tilt angle adjustment.
- Supports SSD (Solid-State Drive) Data Storage Device or HDD.
- The most reliable Fanfree structure for harsh environment.
- Support Win POSReady, WEPOS, XP Pro, Win 7 and Linux environment.



Real mount customer pole display



12" 2nd LCD Display or touch LCD Display with attachment SD-300



Specification	XP-3012H	XP-3015H
Processor	Pine View-D SC 1.66G / 512K Cache CPU, Upgrade to Pine View -D DC 1.66G / 1M Cache CPU (Dual Core)	
System Memory	DDR2 667 MHz,SO-DIMM x 1, max 2 GB, default 1GB	
Storage Device	2.5" SATA HDD or SSD (option)	
Power Supply	12V DC power adaptor, 80W	
Audio	Buzzer Only	
OS support	Windows XP Pro / WEPOS / POSReady / Win 7 / Linux	
<b>Display</b>		
LCD	12" TFT LCD, 1024x768 resolution	15" TFT LCD, 1024x768 resolution
Touch Function	Resistive, 5-Wire, USB Interface	
Brightness Control	By Digital Push Button	
Tilt Adjustment	From 14° to 55°	
<b>Connectivity</b>		
LAN Port	10 / 100 / 1000 Mb	
Serial Port	DB9 x2, RJ-45x1 (RJ-45 to DB9 Cable Option),with 5V support on COM2/COM3	
PS/2 Keyboard	Optional by internal cable	
UPS Port	Yes, Battery Optional	
Standard USB Port	4	
VGA Port	D-SUB, 15 Pin,with 12V power for posiflex LCD Monitor	
CR Port	1, Control 2 CR	
<b>Printer</b>		
3" Thermal Printer	60mm/sec, 80mm paper width	
Cutter	Auto cutter	
<b>Physical Dimension</b>		
Dimension (W x D x H in mm)	325 X 386.2 X 298.1	375 X 386.2 X 395
Weight (N. W. in kg)	6.24	6.83
<b>Environment</b>		
Operation Condition	0°C - 40°C, 20%RH - 90%RH	
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH	
<b>Options</b>		
MSR	Integrated, 2 or 3 tracks and JIS-II	
PD-2606	VFD, 2x20, rear mount	
PD-330	LCD, 2x20, rear mount	
PD-76X4	240x64 dot Graphics LCD, default 200mm pole	
PD-2605	VFD, 2x20, default 200mm pole	
PD-309	LCD, 2x20, default 200mm pole	
SSD	8G minimum	
LM/TM-2212	12" 2nd LCD Display or touch LCD Display with attachment SD-300	
UPS Battery	2300mAh / 12V	

❖ The product information and specifications are subject to change without prior notice.

2010 V.01

## Posiflex Technology, Inc.

6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan  
 Tel: 886 2 2299-1599 Fax: 886 2 2299-1819  
 sales@posiflex.com.tw www.posiflex.com

