



**Revolutionize the customer experience with high-powered, innovative POS technology**



At left part on the front side of base unit, there is a front cover. Pick it up at the bottom notch, there are a CF reader slot and a USB port.



Vertical type LCD panel with easy tilt angle adjustment from 10° to 45°.



Patented Design provides superior heat dissipation.

Data security is a growing market requirement for businesses of all sizes today, and more and more business operation meets the problem with data storage and protection. In order to satisfy the data protection and provides non-stop operation, Posiflex develops the new FT-6615/Raid Terminal, which is built in RAID-1 function with 2 internal 2.5" SATA HDD as well as supports Hot Swap, SteelVine Manager management software, error POP UP notification and SMTP e-mail notification.

This product is suitable for the market segments, which requires for higher level of data protection, for example Public Sector, for 24-hrsx365 days operation Retail, Hospitality etc.

- Support up to 2GB system memory.
- Built-in RAID Function with support of:
  - ◉ RAID 1(Disk Mirroring)
  - ◉ 2xSATA I or SATA II HDD
  - ◉ Hot swap
  - ◉ Management software via SteelVine Manager.
  - ◉ POP UP error notification
  - ◉ SMTP e-mail notification
  - ◉ Windows XP pro, WEPOS, POSReady
- Fan-free design and spill proof and multipurpose construction.
- High quality 15" TFT active matrix LCD panel.
- Brightness controlled by 2 push buttons in front of base unit.
- LED indicators for power status in front bezel, for HDD and LAN status in front of base unit.
- COM port MODEM ring up and LAN wake up function.



Fan-free



CPU



Touch Sensor



15" LCD



UPS

# Posiflex Fan-Free POS Terminal



Specification	FT-6615 / Raid
Processor	Celeron M 1.5GHz W/ 1MB cache
VGA Interface	D-SUB 15 pins
VGA Memory	Share system memory up to 128MB
LCD Display	15" TFT LCD Panel, 1024 x 768 resolution
DRAM Memory	2G DDR2 SDRAM 533MHz, DIMM x 2.
Serial Port	4 x DB9, 1 x RJ45, each with +5V power supply, +12V reserved
Parallel Port	1
CF Card Slot	1
CR Port	1
Standard USB Port	4 (1 in front, 3 in back)
KB Port	1
PS/2 Mouse Port	1
Audio Port	Line-out / Mic-in / W/ 2 W speaker in base unit
Ethernet Port	1x 10/100/1000 MB
UPS Port	1
Touch Controller	USB interface
Touch Sensor	15" Resistive
Extension Slot	1(PCI)
Storage Device	80G SATA HDD x 2
Power Supply	12 VDC power adaptor, 80 W
Fan-free System	Yes
OS Support	WEPOS, POSReady, Windows XP pro
Option peripheral	
PD-2603	VFD, 20x2 Pole Display
PD-308	LCD, 20x2 Pole Display
PD-7623	LCD, 4x15 or 4x30 Pole Display
FA-200	MSR + Optical fingerprint sensor
UPS Battery	2.3AH/12V Lead Acid battery
CDROM	Through USB port
RAID	Built in the HDD interface board
Wireless LAN	802.11 b/g with USB interface
CF Card Slot	Type II, for memory card only

\*\* The product information and specifications are subject to change without prior notice.



Rear mount Customer pole display.



Side mount security attachment, optional MSR and optical finger print sensor.



**Posiflex Technologies, Inc.**  
 6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan, R.O.C.  
 Tel: 886 2 2299-1599 Fax: 886 2 2299-1819  
 sales@posiflex.com.tw www.posiflex.com

