

Fanfree POS System

TX-3000



Wall Mount

POSIFLEX TX-3000 is a compact design of general purpose fan-free system rich in flexibility and adaptability for quiet operation and superior performances. This full function system featured the Intel Pine View technology in a fan-free structure and capable to cover a wide range of applications in KIOSK, KVS, POS, and industrial automation.

This small and fully functional system is suitable for various kinds of segments, such as general retailer, hospitality and restaurant with very limit space.

Features

- Unique fan-free design ideally suited for both harsh and quiet environment.
- Intel Pineview processor with Dual core option offers superior performance.
- Wide range of I/O supports for various peripheral needs and requirements.
- Built-in wall mount capability makes it ideal when space is premium.

Specification	TX-3000
Processor	Pine View-D SC 1.66GHz / 512K Cache CPU, Upgrade to Pine View-D DC 1.66G / 1M Cache CPU (Dual Core)
System Memory	DDR2 667 MHz, SO-DIMM x 1, max 2 GB, default 1GB
Storage Device	2.5" SATA HDD or SSD (optional)
Power Supply	12V DC power adaptor, 60W
Audio	Buzzer Only
OS support	Windows XP Pro / WEPOS / POSReady / Win 7 / Linux
Connectivity	
LAN Port	10 / 100 / 1000 Mb
Serial Port	DB9 x3, RJ-45x1(RJ-45 to DB9 Cable Option), with 5V/12V Support on COM2/COM3
PS/2 Keyboard	Optional by internal cable
Standard USB Port	4
VGA Port	D-SUB, 15 Pin, with 12V power for Posiflex LCD monitor
CR Port	1, Control 2 CR
Physical Dimension	
Dimension (W x D x H in mm)	270 X 253 X 86
Weight (N. W. in kg)	2.29
Environment	
Operation Condition	0°C - 40°C, 20%RH - 90%RH
Storage Condition	(-20°C) - 70°C, 10%RH - 90%RH
Options	
SSD	8GB Minimum

❖ The product information and specifications are subject to change without prior notice.

2010 V.01