



Bar Code Scanner



SK-200

- Button switch in between Omni-directional and single-line scanning capability, ideal for increasing operating efficiency.
- Powerful 20-line scan pattern yields
- 1400 scans per second for Omni-directional scanning
- 74 scans per second for single-line scanning
- Implement with the proprietary real-time hardware decoding technology that ensures instant recognition and decoding barcodes
- Instant working is ready, or can be embedded into other hardware applications via mounting holes at back.
- Optional 3D turning cradle with two joints that maximize the range of adjustment

CD-3830



- Auto discrimination of bar codes
- Ergonomic and light-weight design
- Low power consumption to increase stability
- Interface is easily changeable by switching cable and bar code programming
- High decoding capability but error free
- Connected to many types PC and terminal
- Wide reading aperture
- All models pass drop test with 1.5 meter height
- All models with flash when in continuous reading mode
- Interface:
CD-3830K: KB Interface.
CD-3830U: USB Interface.
CD-3830R: RS232 Interface.

CD-2860



- Auto discrimination of bar codes
- Auto upper/lower case
- Ergonomic and light-weight design
- Low power consumption to increase stability
- Interface can be easily changed by changing cable and scanner setup by bar code reading
- High decoding capability but error free
- Can be connected to many types of PC and terminal
- Wide reading aperture
- All models pass drop test with 1.5 meter height
- CE and FCC Class A approval
- All models with flash when in continuous reading mode
- Interface:
CD-2860K: KB Interface.
CD-2860U: USB Interface.
CD-2860R: RS232 Interface.